

### EYEVEX SAFETY GLOVES

### SPUC 8900 2Q



#### DESCRIPTION

Design: 1/2 Coated Knitwrist  
 Coating: NBR (Nitrile Butadiene Rubber)  
 Coating Texture: Micro-Foam with Non-Slip Grip  
 Liner: UHMWPE-Glass-Nylon, Spandex  
 Weight : 68 to 100 grams/ Pair

#### SIZE SPECIFICATION

Total Length Range: 200 mm to 245 mm  
 Wrist Length: 62 mm to 80 mm  
 Wrist Width: 73 mm to 91 mm  
 Palm Width: 94 mm to 115 mm

#### COLOR

Coating- Black, Liner Blue

#### PROTECTION

Abrasion, cut resistance, dexterity  
 • 2Q (50% of the gloves is coated)

#### APPLICATION

- Maintenance
- Delicate parts handling
- Fabrication
- Automotive

#### CERTIFICATION REQUIREMENT

Skin Health Alliance Dermatologically Accredited: Yes  
 REACH Compliant: Yes  
 Oeko-Tex® Standard 100: Certified  
 Sanitized®: Yes

#### DESIGN STANDARD

- EN 420; 2003+A1: 2009
- EN 388; 2016+ A1: 2018

EN 388:2016  
+A1:2018



OEKO-TEX®  
CONFIDENCE IN TEXTILES  
STANDARD 100



Specification

Pairs per poly bag: 12, Poly bags/ctn: 6, Total pairs/ctn : 72

#### PROTECTION LEVEL RATING

|  |                                  |               |
|--|----------------------------------|---------------|
|  | EN 420 Dexterity                 | > 1000 Cycles |
|  | Abrasion Resistance              | > 800 Cycles  |
|  | Tear Resistance                  | > 75 newtons  |
|  | CN existorme Puncture Resistance | > 60 newtons  |
|  | Cut Resistance ISO               | ≥ 10 Newton   |



#### Mfd. under License from:

EyeveX Safety U.S.A., Inc.  
 800 N King Street, Suite 304 1825  
 Wilmington, DE 19801, USA  
 www.eyevexsafety.com  
 Made in China